NIGERIA MGCP TOPOGRAPHIC MAP 1:50,000

KWIAMBANA SW

EDITION 1-WLP SERIES G764G SHEET 5947-3 NGSA_SHEET 100 SW

One second of longitude equals 30.34m

One second of latitude equals 30.73m

Angwan Nababa
Dandala
Sarkin Baka
Sabon Madada
Sofon-Madada
Maidoruwa
Ungwan-Marafa
Kahato Hill
Goron Dutse Sarki
Karwarwari
Bugana Hills
Buzu Hills
River Kaduna
River Mariga
RIVER MARIGA
Ford
Rocky
Sand and gravel

LEGEND

POPULATED PLACES
Built-up areas: Dense
Sparse or moderate
Not intact
Shantytown; Settlement
Buildings

ROADS
All weather, hard surface: Divided highway: Wide separation — 6 LANES
Narrow separation — 6 LANES
Not intact divided — (CONSTRUCTION)
Four or more lanes wide
Two or three lanes wide
One lane wide
All weather, loose surface:
Four or more lanes wide
Two or three lanes wide
One lane wide — 12km
Fair-weather, loose surface
Street: Hard; Loose — (DESTROYED)
Not intact not divided
Cart track; Trail — 1200m — 1200m
Route markers: International; National — E10 — 55
National motorway; Local — 8 — 20

RAILWAYS
Standard/Broad gauge — Single Track — Multi-track
>= 1.44m (4' 8.5")
Narrow < 1.44m (4' 8.5")
Electrified (standard gauge)
Station; Turntable

BOUNDARIES
International
First-order administrative
Military installation

CULTURAL FEATURES
Building: Important — Police — Prison
Christian; Islam; Judaism
Pagoda; Stupa; Temple
School; Diplomatic; Petrol sale
Hospital; Minaret; Not intact
Fortification; Monument; Ruins
Hut; Holding pen; Surface bunker
Greenhouse; Point; Area

Cemetery: Christian; Islam; Judaism
Buddhism; Unknown
Tower: Communication; Non-communication; Water
Light; Cooling; Water intake
Dish aerial; Smokestack; Flare pipe
Windmill; Wind turbine; Crane
Mooring mast; Ski jump; Rig
Checkpoint; Power substation
Storage tank; Non-water well
Mine/Quarry: Intact; Not intact
UNESCO World Heritage Site
Dam: Hard; Loose
Lock; Sluice/Water gate
Tunnel: Road; Railway
Bridge: Pedestrian; Road; Railway
Culvert: Road; Railway
Wall; Fence
Pipeline: Water — Not water
Surface
Underground
Elevated
Sports ground; Vehicle lot — S — P

VERTICAL OBSTRUCTIONS (VO) (> =46m)
Elevation of obstruction top above sea level — 430
Height of obstruction top above ground level — (70)
Offshore Vertical Obstruction with Helipad
Wind turbine VO: Single; Multiple
VO Power/Communication line
Power line (<46m); Pylon VO
Communication line (<46m)

AERONAUTICAL FEATURES
Water aerodrome
Apron
Taxiway
Intact runway; Stopway
Not intact runway
Helipad: Non-hospital; Hospital — H — H

HYDROGRAPHIC FEATURES — Perennial — Intermittent/Dry
River: Less than 25m wide
25m wide or more
Disappearing; Dissipating
Ditch
Natural pool (spring)
Water well
Lake
Reservoir
Underground aqueduct with qanats
Waterhole; Cistern; Salt evaporator
Rice; Land subject to inundation; Bog/Marsh
Swamp: Other; Nipa/Palm; Mangrove

COASTAL HYDROGRAPHIC FEATURES
Exposed: Rock; Wreck; Reef

VEGETATION
Wood: Deciduous; Evergreen; Mixed
Unknown; Scattered trees; Thicket
Vineyard; Cane; Grassland
Orchard; Cropland: Other; Permanent irrigation
Row of trees; Hedgerow; Tree

HYPSOGRAPHIC FEATURES
Spot elevation: Highest; Normal; Water — 0000 — 9 — 210
Survey point: Geodetic; Benchmark — 1351 — BM — 2645
Mountain pass; Cave mouth — 182
Revetment; Rock; Volcano
Steep terrain face; Levee/Dyke
Cut line; Fill
Sand; Gravel/Moraine
Distorted surface; Other

Sheet History
The Production of Topographic Mapping Sheets with corresponding Geo-databases, using International MGCP Standards, for 340 complete sheets derived from processed satellite imagery (ortho-rectified) mosaic and the WorldDEM. The QA/QC on products incorporated the use of Geospatial Analysis Integrity Tools (GAIT) for geo-database validation by Hexagon. The by-products include anaglyph imaging and MTM50 map sheets (1:50,000 scale) in GeoPDF / GeoTIFF format, generated using Cartographic Production software. The MGCP Topographic Maps were specially prepared as base map data for the use of NGSA in collaboration with the Federal Ministry of Mines and Steel through MinDiver (World Bank assisted project), supported by Woolpert.

NOTES

VECTOR FEATURE DATA CAPTURED FROM 1.5M RESOLUTION SPOT IMAGERY (2018-2022).

A LANE ON THIS MAP IS CONSIDERED TO BE AT LEAST 2.5 METERS (8.2 FEET) WIDE.

ROAD CLASSIFICATION SHOULD BE REFERRED TO WITH CAUTION.

ONLY THROUGH ROUTES ARE CLASSIFIED IN BUILT-UP AREAS.

FORDS ON RIVERS HAVE ONLY BEEN CAPTURED WHERE VISIBLE ON 1.5M RESOLUTION IMAGERY.

CAUTION: NOT ALL COMMUNICATION AND POWER DISTRIBUTION LINES ARE SHOWN.

THE NORMAL (PREDOMINANT) RAILWAY GAUGE IS 1.067 METERS (3' 6").

TO CONVERT METERS TO FEET USE THIS FACTOR: 1 METER = 3.28 FEET.

GROUND REFERENCE POINTS WERE COLLECTED FOR THE GREATER PROJECT AREA AND CAN BE REQUESTED FROM THE NGSA.

MAP INFORMATION AS OF 2022
INTERNATIONAL BOUNDARIES AS OF 2022

TO ENSURE THAT THIS MAP WAS PRINTED AT THE CORRECT SCALE, 10,000 METERS (10 UTM GRID SQUARES) SHOULD MEASURE EXACTLY 20 CENTIMETERS (7.87 INCHES).

One second of longitude equals 30.34m

Scale 1:50,000

Meters 1000 500 0 1 2 3 4 5 Kilometers
1 ½ 0 1 2 3 Statute Miles
1 ½ 0 1 2 3 Nautical Miles

ELEVATIONS IN METERS

CONTOUR INTERVAL 20 METERS
SUPPLEMENTARY CONTOURS 10 METERS

ELLIPSOID . . . . . WORLD GEODETIC SYSTEM 1984
GRID . . . . . 1,000 METER UTM ZONE 32
PROJECTION . . . . . TRANSVERSE MERCATOR
VERTICAL DATUM . . . . . MEAN SEA LEVEL
HORIZONTAL DATUM . . . . . WORLD GEODETIC SYSTEM 1984
FILE PREPARED BY . . . . . Woolpert, Inc.


SAMPLE 1,000 METER GRID SQUARE
SAMPLE POINT
46
45
12
13
100,000 M. SQUARE IDENTIFICATION
KT
GRID ZONE DESIGNATION
32P

100 METER REFERENCE
1. Read large numbers labeling the VERTICAL grid line left of point and estimate tenths (100 meters) from grid line to point: 12 3
2. Read large numbers labeling the HORIZONTAL grid line below point and estimate tenths (100 meters) from grid line to point: 45 6
Example: 123456
WHEN REPORTING ACROSS A 100,000 METER LINE, PREFIX THE 100,000 METER SQUARE IDENTIFICATION IN WHICH THE POINT LIES.
Example: KT123456
WHEN REPORTING OUTSIDE THE GRID ZONE DESIGNATION AREA, PREFIX THE GRID ZONE DESIGNATION.
Example: 32PKT123456

SLOPE GUIDE
PERCENTAGE — DEGREE
15% 8.5°
14% 8.0°
13% 7.4°
12% 6.9°
11% 6.3°
10% 5.7°
9% 5.2°
8% 4.6°
7% 4.0°
6% 3.4°
5% 2.9°
A B C
AB-HORIZONTAL DISTANCE BETWEEN CONTOURS
AC-HORIZONTAL DISTANCE BETWEEN INDEX CONTOURS

GN
MAGNETIC NORTH
GRID NORTH
TRUE NORTH
2020 G-M ANGLE 0° (0 MILS) WEST
GRID CONVERGENCE 0°28' (8 ½ MILS) EAST FOR CENTER OF SHEET
TO CONVERT A MAGNETIC AZIMUTH TO A GRID AZIMUTH SUBTRACT G-M ANGLE
TO CONVERT A GRID AZIMUTH TO A MAGNETIC AZIMUTH ADD G-M ANGLE

BOUNDARIES: NIGERIA



Boundary representation is not necessarily authoritative.


ADJOINING SHEETS

5847-1	5947-4	5947-1
5847-2	5947-3	5947-2
G764 5846-1	5946-4	5946-1

Sheet 5947-3 falls within NC-32-01, 1501A, 1:250,000.

For online purposes only. not necessarily an indication of published maps.

ELEVATION GUIDE



COPYRIGHT RESERVED
Reproduction of all or part of this MGCP/V2 Topographic map standard requires the permission of the NGSA.
© Government of the Federal Republic of Nigeria, 2023

Copies can be obtained from Nigerian Geological Survey Agency, Headquarters, Abuja

LIMITED DISTRIBUTION
Distribution authorized to Ministry of Mines and Steel Development or Producing Agency. Removal of this caveat is prohibited.

WGS 84
CAUTION: VERIFY RED-LIGHT READABILITY

Prepared and published in 2022 by Woolpert, Inc. using MGCP data produced by Woolpert, Inc.

PUBLISHED UNDER THE AUTHORITY OF THE FEDERAL GOVERNMENT OF NIGERIA
Nigerian Geological Survey Agency

KWIAMBANA SW, NIGERIA 5947-3 G764G EDITION 1-WLP

REF. NO. G764X59473